

S.D.O.-L. 10/3/81 A.E.N. (P & D).

REVISIONS		
NO	DESCRIPTION	INITIAL
		SD/ P. D. GAUR 18-9-59 FOR CHIEF ENGINEER
		SD/ P. BHATTACHARYA 19-9-59 FOR C. E. E.
		SD/ P. D. JAIN 14-9-59 X P. D.
		SD/ C. RAMANIAH 3-7-59 A. D. (P & D)

TOE OF SWITCH

R=1450' (441-960)
IIN 12

153'-11 5/16" (46-922)

398'-47 1/16" (121-423)

5'-75'-10 1/8" (23-117)

168'-7" (51-384)

RIM

303'-2 5/8" (92-421)

61'-2" (18-644)

95'-1 7/16" (29-062)

83'-6 1/4" (25-457)

TRAP

50'-0" (15-240)

STARTER

2250' C.S.L. (685-000)

50'-0" (15-240)

83'-6" (25-450)

IIN 8 1/2

IIN 12

R=1458' (444-358)

SAND HUMP

50'-0" (15-240)

50'-0" (15-240)

R=1450' (441-960)

IIN 12

116'-9 1/2" (35-598)

R=2704' (824-179)

IIN 16

TOE OF SWITCH

153'-11 5/16" (46-922)

NOT TO SCALE

COMPARED BY:-