



TRUE COPY

M. A. March
A.E.N. (P.E.D.)

1. FOUNDATIONS TO BE DESIGNED BY THE DIVISION CONCERNED IN ACCORDANCE WITH THE SOIL.
2. LAY OUT OF THE BUILDING SHOULD BE ACCORDING TO THE RELEVANT YARD PLAN. THE DEPTH OF FORMS AND WEIGHT OF PLINTH WILL BE DETERMINED BY THE D.E.M.
3. P.R.C. SHOULD CONSIST OF 1:2:4 CONC. (1:2:4) WITH 2 COATS OF BITUMEN APPLIED OVER IT.
4. P.R.C. SHOULD BE PROVIDED TO ALL WALLS.
5. ALL MAJORITY WORK SHOULD BE IN LINE.
6. EXTERIOR EXCEPT BUILDING JUMPS WHICH ARE 1:4:4.
7. INTERNAL SURFACE OF WALL TO BE LIME RULED.
8. POINTING & INTERNAL SURFACE TO BE PLASTERED & WHITE WASHED.

COMPUTED BY	sd- K. KEMAVAN
DRAWN BY	sd- GULNATI. M.S
CHECKED BY	sd- V.V. DESAI.
TRACED BY	BheirLama
COMPARED BY	Laudhale